



isofast[®] System Membrane Attachment Tool



Application

Productivity tool system for membrane attachment using #15 Dekfast

Features and Benefits

- Each tool cycle installs a fastener and plate simultaneously
- 3 times faster installation
- Stand-up operation reduces back strain and fatigue
- #15 Dekfast fasteners collated on durable polypropylene belting
- 50 fasteners per belt
- Membrane plates stacked on spindles to easily load into feeder

Product Selection

Tools

Material No.	Tool	Fastener Length	Description	Weight
1349029	isofast [®] IF160 Tool	2" to 6"	TOOL-IF160-I-Loan	40
1349071	isofast [®] IF240 Tool	2" to 9"	TOOL-IF240-I-Loan	40

Belted Fasteners

Material No.	Fastener Length	Thread Length*	Description	Carton Wt. (lbs.)	Carton Qty.
1297395	2"	1-3/4"	DF-#15x2-PH3-E0999-BL	21	1,000
1297401	3"	2-3/4"	DF-#15x3-PH3-E0999-BL	31	1,000
1060285	4"	3-3/4"	DF-#15x4-PH3-E0999-BL	21	500
1297411	5"	4"	DF-#15x5-PH3-E0999-BL	25	500
1297420	6"	4"	DF-#15x6-PH3-E0999-BL	30	500
1297427	7"	4"	DF-#15x7-PH3-E0999-BL	35	500
1297433	8"	4"	DF-#15x8-PH3-E0999-BL	39	500
1297438	9"	4"	DF-#15x9-PH3-E0999-BL	44	500

*Note – Thread length measured from tip of the drill point to end of the threads.

Insulation Plate

Material No.	Plate	Description	Carton Wt. (lbs.)	Carton Qty.
792759	IF-2-3/8-AT Membrane Plate	PLT-R-2-3/8-BL	41	500

US
T 800 234 4533
www.sfsintecusa.com

Canada
T 866 847 5400
www.sfsintec.ca

The details stated are results of tests and/or calculations and therefore are non-binding and do not represent warranties or warranted characteristics for not specified applications. All calculations therefore have to be checked and approved by the responsible planner ahead of execution. The user is responsible to assure compliance with all applicable laws and regulations.

isofast[®] System Membrane Attachment Tool

Installation and Application Considerations

Use with:

- #15 Dekfast Phillips head belted fasteners
- isofast[®] round IF-2-3/8-AT membrane plate

Material:

- Steel thickness from 26 ga (0.019 in.) through 18 ga (0.048 in.): Min penetration: 3/4"
- Wood 2x (1-1/2" thick): Min penetration: 1"
- Plywood and OSB: Min through penetration: 3/4"

Specifications and CAD Drawings

Reference Product data sheets for details:

- #15 Dekfast Phillips Head
- isofast[®] round stress plate

Approvals



State of Florida: FL20311

16-0712.08