

Stealth Pre-Assembly Tool and Fasteners



Application

Productivity tool system for insulation attachment using #12 Dekfast and 3" round steel insulation plate

Features and Benefits

- When installed with Stealth tools, productivity increases up to 30% and allows the contractor to install the roof assembly in a more ergonomically correct position versus standard installation methods
- Screw and plate relationship is perpendicular every time allowing for proper and quicker installations
- Pre-assembled fasteners can be placed on the deck or loaded into the Stealth installation tools, giving the contractor the ability to use crew members in other areas of the roof project
- Corded or battery operated DeWalt® screw gun

Product Selection

Tools

Material No.	Tool	Weight
1201245	Stealth tool kit (screw gun not included)	5.0
1652797	Stealth tool kit - battery operated screw gun (battery not included)	7.5
1652798	Stealth tool kit - corded screw gun	8.5
1625510	DeWalt DCB205-2 - 20 Volt 5 Ah DeWalt batteries; pack of 2	3
1625522	DeWalt DCB118 - quick charger for DeWalt 20 Volt battery	2

Pre-Assembled #12 Phillips head Dekfast with 3" round steel plate

Material No.	Fastener Length	Thread Length*	Description	Carton Wt. (lbs.)	Carton Qty.
1367076	1-5/8"	Full	DF-#12x1-5/8-PH3-G3-E0999-BCA	27	500
1367688	2-1/4"	Full	DF-#12x2-1/4-PH3-G3-E0999-BCA	14	250
1658077	3"	Full	DF-#12x3-PH3-G3-E0999-BCA	17	250
1658078	4"	Full	DF-#12x4-PH3-G3-E0999-B	18	250
785806	5"	4"	DF-#12x5-PH3-G3-E0999-B	19	250
785826	6"	4"	DF-#12x6-PH3-G3-E0999-B	20	250
785842	7"	4"	DF-#12x7-PH3-G3-E0999-B	17	200
785858	8"	4"	DF-#12x8-PH3-G3-E0999-B	19	200

*Note – Thread length measured from tip of the drill to end of the threads.

Stealth Pre-Assembly Tool and Fasteners

Installation and Application Considerations

The standard carton package includes one #3 Phillips bit

Use with:

- #12 Dekfast fasteners
- 3" round steel insulation plate

Material:

- Steel thickness from 22 ga (0.030 in.) through 18 ga (0.048 in.): Min penetration: 3/4"
- Wood 2x (1-1/2" thick): Min penetration: 1"
- Plywood and OSB: Min through penetration: 3/4"

Specifications and CAD Drawings

Reference Product data sheets for details:

- #12 Dekfast Phillips Head (DF-#12-PH3)
- 3" round steel insulation plate (PLT-R-3)

Approvals



State of Florida: FL20311

16-0712.08